

SUS304 配管パイプ

定尺4,000mm(一部6,000mmあり)・単位: mm

呼び径		外径	1.5	2.0	2.5	3.0	3.5	4.0	5.0	5.2	5.5	6.0	6.5
A	B		kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P
6	1/8	10.5	1.34	1.69									
8	1/4	13.8	1.84	2.35		3.23							
10	3/8	17.3	2.36	3.05	3.69	4.28							
15	1/2	21.7	3.02	3.92	4.80	5.60							
20	3/4	27.2	3.84	5.04	6.16	7.24							
25	1	34.0	4.84	6.36	7.84	9.28	10.6	12.0					
32	1 1/4	42.7	6.16	8.12	10.0	11.9	13.7	15.4					
40	1 1/2	48.6	7.04	9.28		13.6	15.7	17.8					
50	2	60.5	8.8	11.6		17.2	19.9	22.5	27.6		30.2		
65	2 1/2	76.3		14.8		21.9	25.4	28.8	35.5	36.8			
80	3	89.1		17.4		25.7		33.9	42.0		46.0		
90	3 1/2	101.6		19.8		29.5		38.9	48.0			57.2	
100	4	114.3		22.4		33.3		44.0	54.4			64.8	
125	5	139.8		27.5		40.8	47.6	54.0	67.2			80.0	
150	6	165.2				48.4	56.4	64.4	80.0			95.2	
200	8	216.3				63.6		84.8	105.0			126.0	136.0
250	10	267.4				79.2	92.0	105.0	131.0			156.0	169.0
300	12	318.5				94.4		125.0	156.0			187.0	202.0
350	14	355.6						140.0	175.0			209.0	
400	16	406.4						161.0	201.0			240.0	
450	18	457.2						181.0	226.0			270.0	

※重量を表示しているサイズは即納品です。

寸法の許容差 (配管用 JIS G 3459)

標準重量計算式

外径許容差

外径(mm)	許容差(mm)
30未満	±0.3
30以上	±(外径×1.0%)

長さ許容差

長さ(mm)	許容差(mm)
4,000未満	+10 0
4,000以上	+20 0

鋼種	基本質量(kg)	算式(W/m)
SUS304、304L	7.93	W=0.02491t(D-t)
SUS316、316L	7.98	W=0.02507t(D-t)

厚さ許容差

厚さ(mm)	許容差(mm)
2未満	±0.2
2以上	±(板厚×10%)

真直度許容差

長さ(mm)	許容差(mm)
1,000に対し	1.0以下

